

PŁYTKI OSADCZE DIN 6799

d ₂	d ₁		U							H			D A N E							
			s	Δ	d ₄	a	Δ	weight	d ₂	Δ	m min.	d ₄₂	n	FN (kN)	d ₁	FR (kN)	g	FRg (kN)	n ^{det.} x1000 (rpm)	
	from	to																		
1.2	1.4	2.0	0.30	±0.02	2.90	1.01	±0.04	0.009	1.2	-0.060	0.34	3.0	0.6	0.04	1.5	0.12	0.4	0.06	47	
1.5	2.0	2.5	0.40		3.90	1.28		0.021	1.5		0.44	4.0	0.8	0.07	2.0	0.22	0.6	0.11	42	
1.9	2.5	3.0	0.50		4.40	1.61		0.040	1.9		0.54	4.5	1.0	0.10	2.5	0.35	0.7	0.17	40	
2.3	3.0	4.0	0.60		5.90	1.94		0.069	2.3		0.64	6.0	0.15	3.0	0.50	0.9	0.24	0.24	38	
3.2	4.0	5.0	0.60		6.90	2.70		0.088	3.2		0.64	7.0	0.22	4.0	0.65	0.32	0.32	35		
4.0	5.0	7.0	0.70	±0.03	8.85	3.34	±0.048	0.158	4.0	-0.075	0.74	9.0	1.2	0.25	5.0	0.95	1.0	0.47	32	
5.0	6.0	8.0	0.70		10.85	4.11		0.236	5.0		0.74	11.0	0.90	7.0	1.15	0.60	0.60	28		
6.0	7.0	9.0	0.70		11.80	5.26		0.255	6.0		0.74	12.0	1.10	8.0	1.35	1.1	0.70	25		
7.0	8.0	11.0	0.90		13.80	5.84		0.474	7.0		0.94	14.0	1.5	9.0	1.80	1.3	1.00	22		
8.0	9.0	12.0	1.00		15.75	6.52		0.660	8.0		1.05	16.0	1.8	10.0	2.50	1.5	1.25	20		
9.0	10.0	14.0	1.10	±0.03	18.20	7.63	±0.070	1.000	9.0	-0.090	1.15	18.5	2.0	1.60	11.0	3.00	1.6	1.50	17	
10.0	11.0	15.0	1.20		19.70	8.32		1.120	10.0		1.25	20.0	1.70	12.0	3.50	1.8	1.75	15		
12.0	13.0	18.0	1.30		22.70	10.45		1.770	12.0		1.35	23.0	2.5	3.10	15.0	4.70	1.9	2.30	13	
15.0	16.0	24.0	1.50		28.70	12.61		3.370	15.0		1.55	29.0	3.0	7.00	20.0	7.80	2.2	3.30	11	
19.0	20.0	31.0	1.75		36.50	15.92		6.420	19.0		1.80	37.0	3.5	10.00	25.0	11.00	2.5	3.60	8	
24.0	25.0	38.0	2.00		43.50	21.88		8.550	24.0		2.05	44.0	4.0	13.00	30.0	15.00	3.0	4.00	6	



DIN 6799

