



Wymiar nominalny		2	2.5	3	3.5	4	5	6	8	10	12	14	16	20
	d <sub>1</sub> min.	2.11	2.62	3.12	3.64	4.15	5.15	6.18	8.25	10.30	12.35	14.40	16.40	20.40
stan wolny	d <sub>1</sub> max.	2.21	2.73	3.25	3.79	4.30	5.35	6.40	8.55	10.65	12.75	14.85	16.90	21.00
	d <sub>2</sub> max.	1.90	2.40	2.90	3.40	3.90	4.85	5.85	7.80	9.75	11.70	13.60	15.60	19.60
	a ~	0.70	0.70	0.90	1.00	1.10	1.30	1.50	2.00	2.50	3.00	3.50	4.00	4.50
	s	0.22	0.28	0.33	0.39	0.45	0.56	0.67	0.90	1.10	1.30	1.60	1.80	2.20
	siła kN <sup>1)</sup>	3.50	5.50	7.60	10	13.5	20	30	53	84	120	165	210	340,0
	4													
	5													
+/- 0,25	6													
	8													
	10													
	12													
	14													
	16													
	18													
	20													
	22													
	24													
+/- 0,50	26													
	28													
	30													
	32													
	36													
	40													
	45													
	50													
	55													
	60													
	65													
	70													
	75													
	80													
	85													
+/- 0,75	90													
	95													
	100													
	120													
	140													
	160													
	180													
	200													
tol.	długość	dostępność												

kołki sprężyste zwijane ISO 8748  
(dawniej DIN 7343)