

# PIERŚCIEŃ RW - DIN 7993

d <sub>1</sub>	○					H				d <sub>1</sub>	○					H			
	d <sub>7</sub>	d <sub>3</sub>	Δ	e ≈	$\frac{\rho}{1000}$	d <sub>2</sub>	Δ	r	$\frac{\rho_{det.}}{1000}$ (rpm)		d <sub>7</sub>	d <sub>3</sub>	Δ	e ≈	$\frac{\rho}{1000}$	d <sub>2</sub>	Δ	r	$\frac{\rho_{det.}}{1000}$ (rpm)
4	0.8	3.1		1	0.044	3.2		0.5	175	40	2.5	37.1	-0.6	4	4.64	37.5		1.4	6
5	0.8	4.1	-0.2	1	0.057	4.2		0.5	112	42	2.5	39.0		4	4.87	39.5		1.4	5
6	0.8	5.1		1	0.069	5.2		0.5	77	45	2.5	42.0		4	5.23	42.5	±0.10	1.4	4
7	0.8	6.1		2	0.077	6.2		0.5	57	48	2.5	45.0		4	5.60	45.5		1.4	4
8	0.8	7.1		2	0.090	7.2		0.5	44	50	2.5	47.0		4	5.83	47.5		1.4	4
			-0.3				±0.05						-0.8						
10	0.8	9.1		2	0.115	9.2		0.5	28	55	3.2	51.1		4	10.51	51.8		1.8	4
12	1.0	10.8		3	0.210	11.0		0.6	24	60	3.2	56.1		4	11.50	56.8		1.8	3
14	1.0	12.8		3	0.250	13.0		0.6	18	65	3.2	61.1		4	12.49	61.8		1.8	3
16	1.6	14.2	-0.4	3	0.740	14.4		0.9	22	70	3.2	66.0		5	13.40	66.8		1.8	2
18	1.6	16.2		3	0.830	16.4		0.9	17	75	3.2	71.0		5	14.39	71.8		1.8	2
													-1.0						
20	2.0	17.7		3	1.450	18.0		1.1	18	80	3.2	76.0		5	15.38	76.8		1.8	2
22	2.0	19.7		3	1.600	20.0		1.1	15	85	3.2	81.0		5	16.38	81.8	±0.15	1.8	2
24	2.0	21.7		3	1.780	22.0		1.1	12	90	3.2	86.0		5	17.37	86.8		1.8	1
25	2.0	22.7		3	1.840	23.0		1.1	11	95	3.2	91.0		5	18.36	91.8		1.8	1
26	2.0	23.7	-0.5	3	1.910	24.0		1.1	10	100	3.2	95.8		5	19.31	96.8		1.8	1
							±0.10												
28	2.0	25.7		3	2.070	26.0		1.1	9	105	3.2	100.8		5	20.30	101.8		1.8	1
30	2.0	27.7		3	2.220	28.0		1.1	8	110	3.2	105.8		5	21.29	106.8		1.8	1
32	2.5	29.1		4	3.670	29.5		1.4	9	115	3.2	110.8		5	22.29	111.8		1.8	1
35	2.5	32.1		4	3.980	32.5		1.4	7	120	3.2	115.8		5	23.28	116.8		1.8	1
38	2.5	35.1	-0.6	4	4.400	35.5		1.4	6	125	3.2	120.8		5	24.27	121.8		1.8	1



RW - DIN 7993

